



Magnetization Curve



Hysteresis Law



?

$$P_n = k_n f B_{max}^n V$$

?


Excitation current and Faraday's Law.

*Faraday's Law:

A time varying flux produces an induced voltage in the coil; which is determined by:

$$e = \frac{dd}{dt} = \frac{d(N\phi)}{dt} = N \frac{d\phi}{dt}$$

The polarity of the induced voltage is such that if the winding ends were short-circuited it would produce current that would cause a flux opposing the original flux change.



If there is flux in the magnetic circuit; then a current forms in the coil; which in turn creates opposing flux. (ϕ_i)

$$\phi(t) = \phi_{max} \sin(\omega t)$$

$$e = N \frac{d\phi}{dt}$$

$$e = N\omega \phi_{max} \cos(\omega t)$$

$$e = E_{max} \cos(\omega t)$$


$$e = \frac{\sqrt{2}}{\sqrt{2}} E_{max} \cos(\omega t)$$

$$E_{rms} = \frac{E_{max}}{\sqrt{2}} = \frac{N\omega \phi_{max}}{\sqrt{2}} = \frac{2\pi f N \phi_{max}}{\sqrt{2}}$$

$$= \sqrt{2} \pi f N A B_{max}$$

Excitation Current / flux

Eddy Current



eddy current loss:

$$P = i_{\phi}^2 R$$

To reduce eddy current loss we use thin sheets of lamination material.


$$P_e = k f^2 s^2 B_{max}^2 V$$

f (Hz)
thickness of material.

total volume of material

$$P_{core} = P_e + P_n$$

Inductances



$$\phi = N i$$

$$e = \frac{d\phi}{dt} = N \frac{di}{dt}$$

$$\phi = \frac{F}{R} = \frac{N i}{R}$$

$$e = N \frac{d}{dt} \left(\frac{N i}{R} \right)$$

$$e = \frac{N^2}{R} \cdot \frac{di}{dt}$$

compare with... $v = L \frac{di}{dt}$

$$\therefore L = \frac{N^2}{R}$$


inde

$$L \equiv \frac{\phi}{i}$$

again


$$L = \frac{N\phi}{i} = \frac{N \frac{N i}{R}}{i} = \frac{N^2}{R}$$

Ex:



Find: L & B

SOL



$$R_T = \frac{R_1 R_2}{R_1 + R_2}$$

$$R_1 = \frac{l_1}{\mu_0 A_1} \quad R_2 = \frac{l_2}{\mu_0 A_2}$$

$$\therefore R_T = \frac{1}{\mu_0 \left(\frac{A_2}{l_2} + \frac{A_1}{l_1} \right)}$$

$$\phi = \frac{Ni}{R}$$



$$\phi = \mu_0 Ni \left(\frac{A_1}{l_1} + \frac{A_2}{l_2} \right)$$

$$L = \frac{N\phi}{i} = \mu_0 N^2 \left(\frac{A_1}{l_1} + \frac{A_2}{l_2} \right)$$

$$\phi_1 = \frac{I}{R_1} = \frac{Ni \mu_0 A_1}{l_1}$$

$$B_1 = \frac{\phi_1}{A_1} = \frac{\mu_0 Ni}{l_1}$$

Mutual Inductance



$$\begin{aligned}\phi &= \frac{\mathcal{F}}{R} = \frac{\mathcal{F}_1 + \mathcal{F}_2}{R} = \frac{N_1 i_1 + N_2 i_2}{R} \\ &= \frac{N_1 i_1 + N_2 i_2}{\frac{l}{\mu A}} = \boxed{\frac{\mu A N_1^2}{l} i_1 + \frac{\mu A N_1 N_2}{l} i_2}\end{aligned}$$

$$d_1 = N_1 \phi = \frac{\mu A N_1^2}{l} i_1 + \frac{\mu A N_1 N_2}{l} i_2$$

$$d_1 = d_{11} + d_{12}$$

$$L_{11} = \frac{d_{11}}{i_1} = \frac{\mu A N_1^2}{l}$$

$$L_{12} = \frac{d_{12}}{i_2} = \frac{\mu A N_1 N_2}{l}$$

$$d_2 = N_2 \phi = \frac{\mu A N_1 N_2}{l} i_1 + \frac{\mu A N_2^2}{l} i_2$$

$$d_2 = d_{21} + d_{22}$$

$$L_{21} = \frac{d_{21}}{i_1} = \frac{\mu A N_1 N_2}{l}$$

$$L_{22} = \frac{d_{22}}{i_2} = \frac{\mu A N_2^2}{l}$$